

Hydrophilic levelling putty for use with Bentorub[®]+



• field of application

- Bentostic is used to level rough surfaces in support of the application of Bentorub[®]+

• advantages

- Hydrophilic, swells in contact with water.
- 100% compatible with Bentorub[®]+
- Good sticking power to both the concrete surface and to Bentorub[®]+

• description

- Bentostic is a green hydrophilic levelling putty to be used in conjunction with Bentorub[®]+
- Application of Bentostic to the rough substrate will ensure 100% contact of the Bentorub[®]+
- Bentostic is not a glue and should not be used as the only means of fixing the Bentorub[®]+

• application

Bentostic is applied to the surface with a trowel. Level the putty in order obtain a smooth surface. Press the Bentorub[®]+

• technical data/properties

Property	Value	Norm
Swelling capacity in contact with water	Swells more than 200% of the original dry volume.	Test DNC

• appearance

Green putty.

• consumption

The necessary quantities depend on the length of the various (construction) joints which need to be levelled out before receiving Bentorub[®]+

• packaging

Plastic pail of 5 kg.
1 pallet = 60 pails.

• storage

Bentostic should be stored under cover, clear of the ground. Protect the materials from all sources of moisture and frost.
Shelf life is unlimited.

• health & safety

For full information consult the relevant Material Safety Data Sheet.

All data mentioned on this technical data sheet are product descriptions. They are the result of general experience and experiments and don't take any specific application into account. No further demands may be derived from these data. The manufacturer has the privilege to implement technical changes, which result from new research concerning the material composition and form. To verify that you are holding the latest version of this Technical Data Sheet, please visit www.deneef.eu.

© De Neef Environmental & Chemical group - 19-05-2008-01.